

**70 mm RESIDENTIAL DOOR ORDER/QUOTE FORM**

Please tick for quote only

Page \_\_\_ of \_\_\_.

Aluminium Direct Fax: 01453 827801

E-mail Orders: ali.scheduler@customade.co.uk

Company Name (Acc No): \_\_\_\_\_

Signature: \_\_\_\_\_

Preferred Delivery Date: \_\_\_\_\_

Print Name: \_\_\_\_\_

Order Ref: \_\_\_\_\_

Date: \_\_\_\_\_ E-mail confirmation: \_\_\_\_\_

**System (please tick):** 1.  Contemporary frame - flat sash - internally glazed - square bead  
 White only 3.  Classic-al frame - flat sash - internally glazed - bevel bead

Please Circle Items Required

Please Circle Items Required

(Q) = Selection may need to be upgraded to meet Part Q

**Colour:** White (G) / Grey (7016M) / Black (9005M) /  
 Dual Grey Ext (M) & White Int (G)

**Handle Colour:** White / Gold / Chrome / Black  
 Satin Silver / Grey / Graphite / Antique Black

**Hinge Colour:** Grey / Black / White

**Hinge Guard (Q):** Y / N

**Cylinder (Q):** STD Key-Key / STD Thumb Turn  
 3\* Security Key-Key / 3\* Security Thumb Turn

**Restrictors on open out doors:** Yes / No

**Glass spec (Q):** 28mm DGU / 24mm DGU for Astragal Bar  
 32mm TGU (32mm sq bead only)

**Energy Rating:** 1.8 U-value

**Glass Supply:** Hourglass / Unglazed

**Flat Panel Supply:** Customade / Unglazed

**Astragal bars (24mm units with larger gasket) - please tick:**

Door system 1 - 25mm Flat bar

Door system 3 - 18mm Bevel bar

**Trickle Vent:** White / Black / Grey / Silver

**Part Q Compliant:** Y / N

Note: Low ali thresholds are not weather rated and therefore not recommended for exposed locations.

Location	Design (viewed outside, please show T/vents, midrail dimensions, master door)	Qty In/Out	Sizes (mm) Including Cills & Add-ons	Cill	Thresh	Glass Spec (Tgh, Obs, Lead)	Add-ons 20mm, 42mm or 15mm PVC		Special Requirements
					T/V		T	B	
		Qty:	W	None	Std		T		
					Low Ali		B		
		In	H	150	1250		L		
				190 / 225	2500		R		
		Qty:	W	None	Std		T		
					Low Ali		B		
		In	H	150	1250		L		
				190 / 225	2500		R		
		Qty:	W	None	Std		T		
					Low Ali		B		
		In	H	150	1250		L		
				190 / 225	2500		R		