

VISO FOLD 1000 BI-FOLD DOOR ORDER/QUOTE FORM

Aluminium Direct Fax: 01453 827801

E-mail Orders: ali.scheduler@customade.co.uk



Please tick for quote only

Page ___ of ___.

Company Name (Acc No): _____

Signature: _____

Preferred Delivery Date: _____

Print Name: _____

Order Ref: _____

Date: _____ E-mail confirmation: _____

Please Circle Items Required

(Q) = Selection may need to be upgraded to meet Part Q

Colour: White (G) / Grey (7016M) / Black (9005M) /
 Dual Grey Ext (M) & White Int (G)

Master Door Handle: Lever-Lever only

Slave Door Handle (if applicable): Lever-Lever / Intermediate

Intermediate Handles: Locking / Non-Locking

Lever-Lever Handle Colour: White / Black / Chrome

Grey / Graphite / Satin Silver / Gold

Intermediate Handle Colour: White / Black / Chrome / Grey

Hinge Colour: White / Black (recommended)

'D' Pull Handle (on hinge): White / Black (recommended) / Chrome / Grey

Nickel Cylinder^(Q): STD Key-Key / STD Thumbturn
 3* Security Key-Key / 3* Security Thumbturn
 (T/tutn n/a on shootbolt handles, 3* not keyed alike)

Magnetic Hold Open Catch: None / White / Black /
 Grey / Chrome

Trickle Vent: None / White / Black / Grey / Silver

Glass Supply: Hourglass / Unglazed

Glass Spec (Cl tgh, Softcoat, Argon, Black W/edge)^(Q):

28mm DGU / 36mm TrGU

Glass Special Requirements: _____

Threshold: [] DV14 50mm rebated

[] DV171 15mm flush Ramp: Inside / Outside

[] DV173 20mm flush Ramp: Inside / Outside

[] DV175 30mm flush

Deliver: Assembled / Flat pack frame sashes

Part Q Compliant: Y / N

Note: flush thresholds not weather rated

Note: Mullion dimensions can vary depending on style. External access is only available on bi-folds which have a 'lead' door.

Location	Design (viewed from outside, show master door)	Design (in open position, viewed from above)	Cill	Sizes (mm) Including Cills & Add-ons		20mm Add-ons (required with t/vents)		Special Requirements
				W	H	T	B	
Open in / Open out			None	85	(max 1000mm per sash)	B	T	
			150				L	
			190 / 225	H	(max 2500mm)	R		
Open in / Open out			None	85	(max 1000mm per sash)	B	T	
			150				L	
			190 / 225	H	(max 2500mm)	R		
Open in / Open out			None	85	(max 1000mm per sash)	B	T	
			150				L	
			190 / 225	H	(max 2500mm)	R		